

WAAS CH 78335 W14A	APP CRS 143°	Rwy Idg 4400 TDZE 1798 Apt Elev 1800
--	------------------------	---

RNAV (GPS) RWY 14




SMITH CENTER MUNI (K82)

RNP APCH-GPS.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. When local altimeter setting not received, use Concordia altimeter setting and increase all DA 169 feet and all MDA 180 feet; increase LPV all Cats visibility ¼ SM, LNAV/VNAV all Cats visibility ½ SM, Circling Cat A visibility ¼ SM and Circling Cat B visibility ½ SM. Baro-VNAV and VDP NA with Concordia altimeter setting. Circling Rwy 36 NA at night.

MISSED APPROACH:
Climb to 3700 direct
JUXUL and hold.

AWOS-3PT 118.45	MINNEAPOLIS CENTER 119.4 278.8	UNICOM 122.8 (CTAF) 0
---------------------------	--	---------------------------------



APP CRS
173°

Rwy Idg
TDZE
Apt Elev

3601
1798
1800

RNAV (GPS) RWY 18


SMITH CENTER MUNI (K82)

RNP APCH

Circling to Rwy 36 NA at night. Rwy 18 helicopter visibility reduction below ¾ SM NA. VDP NA when using Concordia altimeter setting. When local altimeter setting not received, use Concordia altimeter setting: increase all MDAs 180 feet and LNAV Cats A/B and Circling Cat A visibility ¼ SM, and Circling Cat B visibility ½ SM.

MISSED APPROACH:
Climb to 3500 direct
ZUVUP and hold.

AWOS-3PT 118.45	MINNEAPOLIS CENTER 119.4 278.8	UNICOM 122.8 (CTAF) 1
--------------------	-----------------------------------	---------------------------------



3500
↑

ZUVUP
✧

2.1 NM to RW18

3.00° TCH 40

3600

173°

353°

3700

4 NM Holding Pattern

CATEGORY	A	B	C	D
LNAV MDA	2500-1	702 (700-1)	NA	
CIRCLING	2500-1 700 (700-1)	2580-1 780 (800-1)	NA	

ELEV 1800 **D** TDZE 1798

173° to RW18

81

50 X 1095

440-175

0.3% UP

0.3% UP


36

MIRL Rwy 14-32 **1**
REIL Rws 14 and 32 **1**

APP CRS	Rwy Idg	3500
353°	TDZE	1798
	Apt Elev	1800

RNAV (GPS) RWY 36

SMITH CENTER MUNI (K82)



NC-2, 22 FEB 2024 to 21 MAR 2024

NC-2, 22 FEB 2024 to 21 MAR 2024



VORTAC TKO	APP CRS	Rwy Idg	N/A
109.8	254°	TDZE	N/A
Chan 35		Apt Elev	1800

VOR-A

SMITH CENTER MUNI (K82)

DME required.	MISSED APPROACH: Climbing left turn to 5000 on TKO VORTAC R-254 to FLAUN/TKO 20 DME and hold, continue climb-in-hold to 5000.
When local altimeter setting not received use Blosser Muni altimeter setting and increase all MDA 180 and Circling Cat B visibility to 1½ SM. Circling to Rwy 36 NA at night.	

AWOS-3PT 118.45	MINNEAPOLIS CENTER 119.4 278.8	UNICOM 122.8 (CTAF)
---------------------------	--	-------------------------------



5000 TKO R-254 FLAUN TKO 20		FLAUN TKO 20		ZIKOM TKO 15	
RZDMP TKO 24.7		3500		254°	
3500		3500		3500	
4.7 NM		5 NM			
CATEGORY	A	B	C	D	
CIRCLING	2400-1 600 (600-1)	2580-1 780 (800-1)	NA		