

LOC I-RGK 110.1	APP CRS 091°	Rwy Idg TDZE Apt Elev 5010 778 778
---------------------------	------------------------	--

ILS or LOC RWY 9



RED WING RGNL (RGK)

ADF Required. When local alimeter setting not received, use South St. Paul alimeter setting; increase S-ILS 9 DA to 1050 feet; increase all MDA 80 feet and visibility S-LOC 9 Cat C/D 1/8 SM and Circling Cat B/C 1/4 SM. For inop MALS, increase S-LOC 9 Cat C/D visibility 1/4 mile. For inop MALS when using South St. Paul alimeter setting, increase S-ILS 9 all Cats visibility 3/8 mile, and S-LOC 9 Cat C/D visibility 3/4 mile.

MALSRLAS

MISSED APPROACH: Climb to 2000 then climbing right turn to 3000 direct REGUE LOM and hold.

AWOS-3 119.25	MINNEAPOLIS APP CON 121.2 335.65	UNICOM 123.05 (CTAF)
-------------------------	--	--------------------------------





21252

RNAV (GPS) RWY 27
RED WING RGNL (RGK)

RFD WING RGNI (RGK)

	DME/DME RNP-0.3 NA. VDP NA with South St. Paul alimeter setting. When local alimeter setting not received, use South St. Paul alimeter setting; increase all MDA 80 feet and visibility LNAV Cat C and Circling Cat C ½ SM and Circling Cat A/B ¼ SM. Helicopter visibility reduction below ¾ SM NA. Inop table does not apply to LNAV Cat C.	ODALS 	MISSED APPROACH: Climb to 3000 direct JUGAN and hold.
---	--	--	--

AWOS-3 119.25	MINNEAPOLIS APP CON 121.2 335.65	UNICOM 123.05 (CTAF) 0
-------------------------	--	----------------------------------



RED WING RGNL (RGK)

RNAV (GPS) RWY 27

NC-1, 22 FEB 2024 to 21 MAR 2024

WAAS CH 56526 W09A	APP CRS 091°	Rwy Idg 5010 TDZE 778 Apt Elev 778
--	------------------------	---


RNAV (GPS) RWY 9
RED WING RGNL (RGK)

⚠ Baro-VNAV NA when using South St. Paul altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 38°C (100°F). DME/DME RNP-0.3 NA. VDP NA with South St. Paul altimeter setting. When local altimeter setting not received, use South St. Paul altimeter setting; increase LPV DA to 1050 feet, LNAV/VNAV DA to 1232 feet, and visibility LNAV/VNAV 3/8 SM all Cats; increase all MDA 80 feet and visibility LNAV Cat B/C/D and Circling Cat B/C 1/4 SM. For inop MALSR, increase LNAV Cat C/D visibility 3/8 mile. For inop MALSR when using South St. Paul altimeter setting, increase LPV visibility 3/8 mile all Cats, LNAV/VNAV all Cats and LNAV Cat C/D visibility 3/8 mile.

MALSR

MISSED APPROACH:
Climb to 3000 direct ZAMLU and hold.

AWOS-3 119.25	MINNEAPOLIS APP CON 121.2 335.65	UNICOM 123.05 (CTAF) 0
-------------------------	--	----------------------------------



4 NM Holding Pattern JUGAN

GP 3.00° TCH 50

ETEXTY 2700

3000 ZAMLU

*LNAV only

6.9 NM 4.5 NM 1.4 NM

CATEGORY	A	B	C	D
LPV DA	978-1/2		200 (200-1/2)	
LNAV/VNAV DA	1160-3/4		382 (400-3/4)	
LNAV MDA	1260-1/2 482 (500-1/2)		1260-1 482 (500-1)	
CIRCLING	1480-1 702 (800-1)	1520-1 742 (800-1)	1640-2 1/2 862 (900-2 1/2)	1780-3 1002 (1100-3)

HIRL Rwy 9-27 0