

ALTUS, OKLAHOMA

ILS or LOC RWY 18L

LOC I-RUK

110.55

APCH CRS

175°

Rwy Idg TDZE

1382

Arprt Elev

1382

AL-482 [USAF]

ALTUS AFB (KLTS)

DME or RADAR required.

▼

* When ALS inop, increase RVR to 55 and vis to 1 mile.

** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile, CAT CDE vis to 1½ miles.

ATIS ★

109.8 273.5

FORT WORTH CENTER

133.5 350.35

APP CON

125.1 353.7

TOWER ★

119.65 254.4

GND CON

121.85 275.8

CLNC DEL

120.65 284.7

*** Circling not authorized W of Rwy 18R-36L.

LTS 17

2570

HOLD 9000 4000

ATC RADAR Required for holding

1792

1886

1665

1580

1526

1504

1775

ALTUS 109.8 LTS

Chan 35

2049

1720

1664

1720

352°

172°

LTS 16

R-358

(IF/IAF) JEPKI LTS 12

WOTSI RADAR LTS 9

JABLI RADAR LTS 5.8

ZEXIX LTS 3.2

2110

LOCALIZER 110.55 I-RUK

CIPNO LTS 11

HOLD 7000 4000

MSA LTS 2.5 NM

3800

3200

120°

310°

EMERG SAFE ALT 100 NM 4900

ELEV 1382

TDZE 1382

4000

LTS R-172

CIPNO LTS 11

VORTAC

ZEXIX 3.2

JABLI 5.8 RADAR

WOTSI 2 RADAR

JEPKI 12

17

358°

178°

9000 4000

GS 3.00° TCH 47

CATEGORY

A

B

C

D

E

S-ILS 18L

1582/40

200

(200-¾)

S-LOC 18L *

1760/40

378

(400-¾)

*** CIRCLING

1780-1 398 (400-1)

1840-1 458 (500-1)

1880-1½ 498 (500-1½)

2080-2¼ 698 (700-2¼)

2180-2¾ 798 (800-2¾)

WITHOUT LAST STEPDOWN FIX

S-LOC 18L **

2040/40 658 (700-¾)

2040-1½ 658 (700-1½)

2080-2¼ 698 (700-2¼)

2180-2¾ 798 (800-2¾)

*** CIRCLING

2040-1 658 (700-1)

2040-1½ 658 (700-1½)

2080-2¼ 698 (700-2¼)

2180-2¾ 798 (800-2¾)

SC-1, 22 FEB 2024 to 21 MAR 2024

SC-1, 22 FEB 2024 to 21 MAR 2024