

LOC/DME I-ONA 109.35 Chan 30 (Y)	APP CRS 300°	Rwy Idg TDZE 656 Apt Elev 656
--	------------------------	---

ILS Y or LOC Y RWY 30

WINONA MUNI-MAX CONRAD FIELD (ONA)

DME required.

VDP N/A with La Crosse altimeter setting. When local altimeter setting not received, use La Crosse altimeter setting and increase S-ILS 30 DA to 1127 and all visibilities 1/8 mile, increase all MDA 60 feet, and visibility S-LOC 30 Cat C/D 1/8 mile, and Circling Cat B 1/4 mile. For inop ALS, increase S-ILS 30 all Cats visibility to 1 3/8 mile, increase S-LOC 30 Cats C/D visibility to 1 3/8 mile. For inop ALS when using La Crosse altimeter setting, increase S-ILS 30 all Cats visibility to 1 3/8 mile, increase S-LOC 30 Cats C/D visibility to 1 3/8 mile.

MALSR

MISSED APPROACH:
Climb to 1800 then climbing left turn to 3000 on RST VOR/ DME R-056 to VUZID INT and hold.

AWOS-3 118.075	MINNEAPOLIS CENTER 128.6 363.0	UNICOM 122.8 (CTAF)
--------------------------	--	-------------------------------

ELEV 656 D TDZE 656

REIL Rwy 12
MIRL Rwy 12-30

1800	3000	VUZID	Δ	Δ2045
↑	RST R-056	Δ		
*LOC only	*I-ONA	WABNY I-ONA	ALEYU INT I-ONA	
I-ONA 0.9	I-ONA 2.5	2400	2400	3100
1.6 NM	3.7 NM	6 NM		GS 3.00° TCH 50
CATEGORY	A	B	C	D
S-ILS 30	1074-1 8 418 (500-1 8)			
S-LOC 30	1220- 1 2 564 (600- 1 2)	1220-1 4 564 (600-1 4)		
CIRCLING	1560-1 1 4 904 (1000-1 1 4)	1600-1 1 4 944 (1000-1 1 4)	1780-3 1124 (1200-3)	1980-3 1324 (1400-3)

WINONA, MINNESOTA

44°05'N-91°43'W

WINONA MUNI-MAX CONRAD FIELD (ONA)

Orig-B 11AUG22

ILS Y or LOC Y RWY 30