

WAAS CH 97715 W09A	APP CRS 091°	Rwy Idg TDZE 1623 Apt Elev 1623
--	------------------------	---

RNAV (GPS) RWY 9

RHINELANDER/ONEIDA COUNTY(RHI)

RNP APCH + GPS.

MAISLR

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. For inop ALS, increase LNAV Cats C/D visibility to 1½ SM.

MISSED APPROACH:
Climb to 4500 direct
BADAY and hold.

ASOS 126.825	MINNEAPOLIS CENTER 133.65 281.5	UNICOM 123.0 (CTAF) 1
------------------------	---	--

ELEV 1623

D TDZE 1623

4 NM Holding Pattern

ECANA

GATRE

ZINGI

RW09

6000

3500

GP 3.00°

TCH 52

271°

091°

091°

091°

091°

6.4 NM

3.7 NM

0.8 NM

1.1 NM

4500

BADAY

091° to RW09

6800 X 150

0.4% UP

5201

1659

33

CATEGORY	A	B	C	D
LPV DA	1823-½		200 (200-½)	
LNAV/VNAV DA	2050-¾		427 (500-¾)	
LNAV MDA	2040-½	417 (500-½)	2040-¾	417 (500-¾)
C CIRCLING	2100-1 477 (500-1)	2260-1 637 (700-1)	2260-1¾ 637 (700-1¾)	2280-2 657 (700-2)

HIRL Rwy 9-27 and 15-33

REIL Rwy 15, 27 and 33

RHINELANDER, WISCONSIN

Amdt 1E 08SEP22

45°38'N-89°28'W

RHINELANDER/ONEIDA COUNTY (RHI)

RNAV (GPS) RWY 9