

WAAS CH 58322 W18A	APP CRS 178°	Rwy Idg TDZE Apt Elev	5005 140 140
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 18

CLEVELAND MUNI (RNV)



▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Greenville altimeter setting and increase LPV DA to 438, LNAV/VNAV DA to 597, and all MDA 60 feet; increase LPV all Cats and LNAV Cats C/D visibility ½ mile, increase LNAV/VNAV all Cats visibility ¼ mile. Baro-VNAV and VDP NA when using Greenville altimeter setting. Rwy 18 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 2100 direct
EWOP and hold.

AWOS-3PT 124.175	MEMPHIS CENTER 135.875 269.35	UNICOM 122.725 (CTAF) ①
----------------------------	---	-----------------------------------



4 NM Holding Pattern		JOMEM	ZEMAK	WAMVI	RW18	
2100 ← 358°		178° →	2100	*1120	*1 NM to RW18	
GP 3.00°		TCH 42	6.6 NM	3 NM	2 NM	1 NM
CATEGORY	A	B	C	D		
LPV DA	390-7 ⁸ / ₈		250 (300-7 ⁸ / ₈)			
LNAV/VNAV DA	549-13 ⁸ / ₈		409 (500-13 ⁸ / ₈)			
LNAV MDA	500-1		360 (400-1)			
CIRCLING	600-1	460 (500-1)	900-2 ¹ / ₄ 760 (800-2 ¹ / ₄)	900-2 ¹ / ₂ 760 (800-2 ¹ / ₂)		

SC-4, 22 FEB 2024 to 21 MAR 2024

SC-4, 22 FEB 2024 to 21 MAR 2024