

WAAS CH 86608 W35A	APP CRS 345°	Rwy Idg 5002 TDZE 610 Apt Elev 610
--	------------------------	---

RNAV (GPS) RWY 35
ROBERT SIBLEY (SZY)


RNP-APCH - GPS.	
-----------------	--

NA Baro-VNAV NA when using Mc Kellar-Sipes Rgnl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 47°C. Helicopter visibility reduction below 1 SM not authorized. When local altimeter setting not received, use Mc Kellar-Sipes Rgnl altimeter setting: increase LPV DA to 1042 and all visibilities $\frac{1}{4}$ SM, increase LNAV/VNAV DA to 1084 and all visibilities $\frac{1}{2}$ SM; increase all MDAs 100 feet and LNAV visibility Cat C and D and Circling visibility Cat D $\frac{1}{4}$ SM. Straight-in Rwy 35 NA at night. Circling Rwy 17, 35 NA at night.


MISSED APPROACH:
Climb to 2600 direct
YIPUB and hold.

AWOS-3 118,425	MEMPHIS CENTER 124.35 318.1	UNICOM 122.7 (CTAF) 0
--------------------------	---------------------------------------	---------------------------------

MISSED APCH FIX



ELEV 610		TDZE 610
----------	--	----------



REIL Rwy 17 and 35

MIRL Rwy 17-35 (1)

VGSi and RNAV glidepath not coincident
(VGSi Angle 4.00°/TCH 29).

ZABAB 4 NM Holding Pattern

2600

165°

345°

2100

PUYBI

RW35

4.5 NM

6 NM

GP 3.00°
TCH 40

CATEGORY	A	B	C	D
LPV DA	944-1¼ 334 (400-1¼)			
LNAV/ VNAV DA	986-1¼ 376 (400-1¼)			
LNAV MDA	980-1 370 (400-1)			980-1¼ 370 (700-2¼)
CIRCLING	1060-1 450 (500-1)	1080-1 470 (500-1)	1080-1½ 470 (500-1½)	1300-2¼ 690 (700-2¼)