



WAAS CH 78101 W16A	APP CRS 160°	Rwy Idg TDZE Apt Elev	7000 682 682
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 16

DRAUGHON-MILLER CENTRAL TEXAS RGNL (TPL)

RNP APCH - GPS.		MALSR	MISSED APPROACH: Climb to 3600 direct FADXY and on track 074° to BARBA and hold, continue climb-in-hold to 3600.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM and LNAV Cats C/D visibility to ⅞ SM.			

AWOS-3PT 134.975	GRAY APP CON 120.075 370.0	CLNC DEL 125.9	UNICOM 123.0 (CTAF)
----------------------------	--------------------------------------	--------------------------	---



4 NM Holding Pattern		IHS AZ	IFDOH	3600	FADXY	tr 074°	BARBA
6000 ← 340°		3000 → 160°	2400	CUMIX 1.7 NM to RW16			
GP 3.00° TCH 45		2400	1260	0.7 NM to RW16			
		6 NM	3.6 NM	1 NM	0.7		
CATEGORY	A	B	C	D			
LPV DA	882-½		200 (200-½)				
LNAV/VNAV DA	932-½		250 (300-½)				
LNAV MDA	960-½		278 (300-½)				
CIRCLING	1140-1	1200-1	1280-1½	1420-2¼			
	458 (500-1)	518 (600-1)	598 (600-1½)	738 (800-2¼)			