

LOC/DME I-YKM

110.1

APP CRS

274°

Rwy Idg TDZE

7604 1068

Chan 38

Apt Elev 1099

ILS or LOC RWY 27

YAKIMA AIR TRML/MCALLISTER FLD (YKM)

DME required for procedure entry. DME required for LOC only.

When local altimeter setting not received, procedure NA. Circling NA south of Rws 9 and 27. For inop ALS, increase S-LOC 27 Cats C/D visibility to 2 SM. For inop ALS, increase S-ILS 27 all Cats visibility to 1½ SM. #RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 2900 then climbing right turn to 4900 direct YKM. VORTAC and hold, continue climb-in-hold to 4900. # Missed approach requires minimum climb of 275 feet per NM to 3600.

ATIS	SPOKANE APP CON*	YAKIMA TOWER*	GND CON	CLNC DEL	UNICOM
125.25	123.8 263.15	133.25 (CTAF) 0 257.8	121.9	121.9	122.95

ELEV 1099

TDZE 1068

2900

4900

YKM

6000

3800

2780

2280

FIGRU I-YKM [6.7]

CISUS I-YKM [5.1]

I-YKM [3.5]

I-YKM [1.4]

2.1 NM

1.6 NM

1.6 NM

3.2 NM

2.5 NM

094°

274°

4300

4000

3800

2780

2280

GS 3.00°

TCH 56

Remain within 10 NM

CATEGORY	A	B	C	D
S-ILS 27 #	1268/24	200 (200-½)		
S-ILS 27	1713-1½	645 (700-1½)		
S-LOC 27	1780/24	712 (700-½)	1780-1½	712 (700-1½)
CIRCLING	1780-1	681 (700-1)	1940-2½	2280-3
			841 (900-2½)	1181 (1200-3)

MIRL Rwy 4-22

HIRL Rwy 9-27

REIL Rws 4, 9, and 22

YAKIMA, WASHINGTON

Amdt 1B 06OCT22

YAKIMA AIR TRML/MCALLISTER FLD (YKM)

46°34'N-120°33'W

ILS or LOC RWY 27